

AUGER MODELS

Feed Mechanism: 5-1/4 inch full length steel variable pitch auger, stainless steel trough

Motor: Two 12V direct drive gear motors (3/4 HP for auger and 1/2 HP for spinner)

PRO1500

Capacity: 1.5 cubic yards (6 feet)

Application: Minimum 10,000 lb GVW

PRO2000

Capacity: 2 cubic yards (8 feet)

Application: Minimum 10,000 lb GVW

PRO2500

Capacity: 2.5 cubic yards (8 feet)

Application: Minimum 13,000 lb GVW

<i>Bulk Salt</i>	<i>Bulk Sand</i>	<i>Bagged #1 Rock Salt</i>	<i>50 / 50 Salt / Sand</i>
✓		✓	✓

CHAIN MODELS

Feed Mechanism: 12 inch wide all steel pintle chain conveyor and stainless steel trough

Motor: Two 12V direct drive gear motors (3/4 HP for chain and 1/2 HP for spinner)

PRO1500CH

Capacity: 1.5 cubic yards (6 feet)

Application: Minimum 10,000 lb GVW

PRO2000CH

Capacity: 2 cubic yards (8 feet)

Application: Minimum 10,000 lb GVW

PRO2500CH

Capacity: 2.5 cubic yards (8 feet)

Application: Minimum 13,000 lb GVW

<i>Bulk Salt</i>	<i>Bulk Sand</i>	<i>Bagged #1 Rock Salt</i>	<i>50 / 50 Salt / Sand</i>
✓	✓	✓	✓