ELECTRIC SLIDE-IN SPREADERS

5-1/4 Inch Auger or 12 Inch Pintle Chain Feed



FEATURES

Spread Range: 2-30 feet

Construction: 304 stainless steel hopper

Application: 3/4 and 1 ton pickup, flatbed or dump truck

Additional Features: • Top screen

Stainless steel inverted V

INCLUDED ACCESSORIES

• Tie-downs kit

CONTROLLER

Variable speed controller

Independent auger / conveyor and spinner control

Vibrator control



3016934



1470601SS

Capacity: 2 cubic yards (8 feet) **Application:** Minimum 10,000 lb GVW

Feed Mechanism: 5-1/4 inch full length steel variable pitch auger, stainless steel trough

Motor: Two 12V direct drive gear motors (3/4 HP for auger and 1/2 HP for spinner)

Chute Assembly: Spinner assembly includes side-swing feature for easy cleaning, storage and bulk unloading





CHAIN MODELS

Feed Mechanism: 12 inch wide all steel pintle chain conveyor

Feed Gate: Lever operated with friction lock for accurate adjustment

Motor: Two 12V direct drive gear motors (3/4 HP for chain and 1/2 HP for spinner)

Chute Assembly: 14 inch polymer disc with six fins, chute adjusts 11.5 inches

1400701SS

— 1400601SS

Capacity: 1.5 cubic yards (6 feet) **Capacity:** 2 cubic yards (8 feet) **Application:** Minimum 10,000 lb GVW Application: Minimum 10,000 lb GVW

Bulk	lce	Bagged #1	50 / 50
Salt	Melt	Rock Salt	Salt / Sand
/	/	/	/